


Copyright MWE NA Inc., all rights reserved. Reproduction or other use of these designs without written consent from MWE NA Inc. is prohibited.

All ladder systems require reinforced walls, cabinets, or shelving.



SL.6011.AK






MME[®]
NORTH AMERICA

Prepared By: CDA | JRT

Copyright MWE NA Inc., all rights reserved. Reproduction or other use of these designs without written consent from MWE NA Inc. is prohibited.

Copyright MWE NA Inc., all rights reserved. Reproduction or other use of these designs without written consent from MWE NA Inc. is prohibited.



A diagram of a curved track with a dashed center line and solid red boundary lines. A blue vehicle is shown on the track, with a curved arrow indicating a 180-degree turn. The track is bordered by a grey textured area on the right.

Vario Ladder SL.6004.AK.E

Date Prepared: October 2018

Prepared By: CDA | JRT




NORTH AMERICA

Email: info@mwe-na.com



www.mve-na.com

Technical drawings are subject to change without notice.
All millimeter dimensions are exact and supersede inch conversions.

Ladder height at or above 3000mm [118 1/8"]
require safety slide rails SL.6052.AK



Example:
- Curved rail
- Rail radius on request



Copyright MWE NA Inc. all rights reserved. Reproduction or other use of these designs without written consent from MWE NA Inc. is prohibited.
All ladder systems require reinforced walls, cabinets, or shelving.


Vario Ladder SL.6004.AK.H

Date Prepared: October 2018





Prepared By: CDA | JRT

Technical drawings are subject to change without notice.
All millimeter dimensions are exact and supersede inch conversions.

Ladder height at or above 3000mm [118 1/8"]
require safety side rails SL.6052.KL



Example:
- Curved rail
- Rail radius on request



Copyright MWE NA Inc. all rights reserved. Reproduction or other use of these designs without written consent from MWE NA Inc is prohibited.
All ladder systems require reinforced walls, cabinets, or shelving.





Vario Ladder SL.6004.KL

Date Prepared: October 2018


Prepared By: CDA | JRT

Technical drawings are subject to change without notice.
All millimeter dimensions are exact and supersede inch conversions.

Ladder height at or above 3000mm [118 1/8"]
require safety side rails SL.6052.KL



Example:
- Curved rail
- Rail radius on request



Vario Ladder SL.6004.KL.E



Date Prepared: October 2018

Prepared By: CDA | JRT


Copyright MWE NA Inc. all rights reserved. Reproduction or other use of these designs without written consent from MWE NA Inc is prohibited.
All ladder systems require reinforced walls, cabinets, or shelving.

Technical drawings are subject to change without notice.
All millimeter dimensions are exact and supersede inch conversions.

Ladder height at or above 3000mm [118 1/8"]
require safety side rails SL.6052.KL



Copyright MME NA Inc. all rights reserved. Reproduction or other use of these designs without written consent from MME NA Inc is prohibited.
All ladder systems require reinforced walls, cabinets, or shelving.



Vario Ladder SL.6004.KL.H

Date Prepared: October 2018

Prepared By: CDA | JRT